

Package: sourcetools (via r-universe)

October 10, 2026

Type Package
Title Tools for Reading, Tokenizing and Parsing R Code
Version 0.1.7-9000
Author Kevin Ushey
Maintainer Kevin Ushey <kevinushey@gmail.com>
Description Tools for Reading, Tokenizing and Parsing R Code.
License MIT + file LICENSE
LazyData TRUE
Depends R (>= 3.0.2)
Suggests testthat
LinkingTo testthat (>= 1.0.2)
RoxygenNote 7.1.1
BugReports <https://github.com/kevinushey/sourcetools/issues>
Encoding UTF-8
Config/pak/sysreqs cmake make libuv1-dev
Repository <https://kevinushey.r-universe.dev>
Date/Publication 2025-05-06 23:04:17 UTC
RemoteUrl <https://github.com/kevinushey/sourcetools>
RemoteRef HEAD
RemoteSha 8f060cbd8ba5a930505645b7d10d553860588343

Contents

read	2
register_routines	2
tokenize_file	3
validate_syntax	4
Index	5

read	<i>Read the Contents of a File</i>
------	------------------------------------

Description

Read the contents of a file into a string (or, in the case of `read_lines`, a vector of strings).

Usage

```
read(path)
read_lines(path)
read_bytes(path)
read_lines_bytes(path)
```

Arguments

path	A file path.
------	--------------

register_routines	<i>Register Native Routines</i>
-------------------	---------------------------------

Description

Discover and register native routines in a package. Functions to be registered should be prefixed with the `'// [[export(<methods>)]]'` attribute.

Usage

```
register_routines(package = ".", prefix = "C_", dynamic.symbols = FALSE)
```

Arguments

package	The path to an R package.
prefix	The prefix to assign to the R objects generated that map to each routine.
dynamic.symbols	Boolean; should dynamic symbol lookup be enabled?

tokenize_file	<i>Tokenize R Code</i>
---------------	------------------------

Description

Tools for tokenizing R code.

Usage

```
tokenize_file(path)
```

```
tokenize_string(string)
```

```
tokenize(file = "", text = NULL)
```

Arguments

file, path A file path.

text, string R code as a character vector of length one.

Value

A data.frame with the following columns:

value	The token's contents, as a string.
row	The row where the token is located.
column	The column where the token is located.
type	The token type, as a string.

Note

Line numbers are determined by existence of the `\n` line feed character, under the assumption that code being tokenized will use either `\n` to indicate newlines (as on modern Unix systems), or `\r\n` as on Windows.

Examples

```
tokenize_string("x <- 1 + 2")
```

validate_syntax	<i>Find Syntax Errors</i>
-----------------	---------------------------

Description

Find syntax errors in a string of R code.

Usage

```
validate_syntax(string)
```

Arguments

string	A character vector (of length one).
--------	-------------------------------------

Index

`read`, [2](#)
`read_bytes (read)`, [2](#)
`read_lines (read)`, [2](#)
`read_lines_bytes (read)`, [2](#)
`register_routines`, [2](#)

`tokenize (tokenize_file)`, [3](#)
`tokenize_file`, [3](#)
`tokenize_string (tokenize_file)`, [3](#)

`validate_syntax`, [4](#)